We cl	aim:
1.	A coolant composition to be blended in coolant for cooling a fuel cell stack,
comp	rising a base material and a dye which maintains the electrical conductivity of the
coola	nt at 10 μS/cm or lower at 25°C.
2.	A coolant composition to be blended in coolant for cooling a fuel cell stack,
comp	rising a base material and a dye which passes through a cation or anion exchanger
provic	led in the fuel cell stack.
2	The explort composition apporting to claim 1 or 2, whorein the dve does not change
3.	The coolant composition according to claim 1 or 2, wherein the dye does not change
or nar	dly changes the hue of the coolant at 100°C.

– 3216/1 Page 12 –

The coolant composition according to any one of claims 1 to 3, wherein the dye is

selected from the group consisting of azoic dyes, sulfuric dyes, vats, oil-soluble dyes,

4.

disperse dyes and combinations thereof, which do not have a sulfonic acid group or a carboxyl group.		
<ol> <li>The coolant composition according to claim 4, wherein the azoic dye is Azoic Blue</li> <li>as defined by SDC.</li> </ol>		
6. The coolant composition according to claim 4, wherein the sulfuric dye is selected from the group consisting of Sulphur Blue 3, Sulphur Blue 6, Sulphur Blue 7, Sulphur Blue 9, Sulphur Blue 13, Sulphur Green 1, Sulphur Red 2, Sulphur Red 3, Sulphur Red 5 and Sulphur Red 7 as defined by SDC.		
7. The coolant composition according to claim 4, wherein the vat is selected from the group consisting of Vat Blue 1, Vat Blue 3, Vat Blue 4, Vat Blue 5, Vat Blue 6, Vat Blue 12,		
– 3216/1 Page 13 –		

Vat Blue 13, Vat Blue 14, Vat Blue 18, Vat Blue 19, Vat Blue 20, Vat Blue 35, Vat Blue 41, Vat Green 1 and Vat Red 1 as defined by SDC.

8. The coolant composition according to claim 4, wherein the oil-soluble dye is selected from the group consisting of Solv. Blue 36, Solv. Blue 63, Solv. Green 3, Solv. Red 23, Solv. Red 43, Solv. Red 48, Solv. Red 72, Solv. Orange 2, Solv. Yellow 33 and Solv. Yellow 73 as defined by SDC.

9. The coolant composition according to claim 4, wherein the disperse dye is selected from the group consisting of Disperse Blue 1, Disperse Blue 3, Disperse Blue 14, Disperse Orange 1, Disperse Orange 3, Disperse Orange 11, Disperse Orange 13, Disperse Orange 25, Disperse Red 1, Disperse Red 13, Disperse Red 19, Disperse Yellow 3, and Disperse Yellow 9 as defined by SDC.

10. The	e coolant composition according to any one of claims 1 to 9, wherein the dye is	
contained	0.00001 to 0.1 % by weight.	
11. The	e coolant composition according to any one of claims 1 to 10, wherein the base	
material is selected from the group consisting of water, glycols, alcohols, glycol ethers and		
mixtures thereof.		
40 Th.	a and and a compacition according to any one of plains 4 to 44. fourth or comparing a	
	e coolant composition according to any one of claims 1 to 11, further comprising	
ana	anti-rust additive and an anti-foam agent.	
	– 3216/1 Page 15 –	